Phoenix Tapes®
Simbolul Calității

Street Drumul Gilaului no. 5N
District 4, Bucharest
E-mail: office@phoenixtapes.ro
Phone: +4 021.335.1172
Mobile: +4 0729.012.783

TECHNICAL DATA SHEET 2981

CONSTRUCTION

Carrier: Tissue paper
Adhesive: Solvent acrylic
Liner: Silicone release PE-coated paper, amber colour

TYPICAL PHYSICAL PROPERTIES

Total Thickness (without liner): 140±10% mic
Thickness of tissue carrier: 30mic
Thickness of glue: 130mic, 130g/m2
Thickness of release paper: 75mic, 90g/m2
Peel Adhesion (180°): 21.7N/25mm
Tack Rolling Ball: ≤ 2 cm
Tensile Strength: N/A N/25mm
Application Temperature: 8→38 °C
Heat Resistance: -10→100 °C

PACKING:

Core I.D.: 5" (76mm±1)
Log Roll: 1040mm x 50M
Packaging: Wrapped with corrugated cardboard

REMARKS

(1) The data above are typical results and subject to change without notice
(2) Tolerance: Weight and Thickness: ±10%; Width: ±3mm;
Length: Cut Roll & Log Roll ±0.3m.
(3) The products should be stored at room temperature and be kept away from wet and/or heat source.
(4) It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
(5) The users should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for their special purpose and technique.

SUGESTED APLICATIONS

- suitable for glossy/matte paper and non-woven surfaces
- for general nameplate adhesion
- cardboard boxes (insulated and non-insulated), corrugated fiberboard, bleached and unbleached solid cardboard, white lined clipboard
- cardboard displays
- cardboard tubes
- various types of cards: business cards, aperture cards, postcards, playing cards

NOTE:

All data contained in this document are average values, they should not be used for specification purpose. All statements, technical information and recommendations contained are base upon tests that we believe are reliable, but we are strongly recommend clients should do their own tests and decide whether the product is fit for a particular purpose or the method of application.

IMPORTANT:

Phoenix Invest makes no other warranties, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or any implied warranty arising out of a course of dealing, custom or usage of trade.

REMEDY & LIMITATION OF LIABILITY:

If the Phoenix Invest product is proved be defective within the warranty period, your exclusive remedy and Phoenix Invest's and seller's sole obligation will be, at Phoenix Invest's to replace or refund the purchase price.

STORAGE

Products should be stored at temperature 8°C-38°C and relative humidity 50%-70%.
The shelf life is 2 (two) years. Avoid prolonged exposure to direct sunlight.

AVAILABILITY

Widths: 6 mm, 9 mm, 12 mm, 25 mm, 50 mm, 100 mm (other widths available)
Lengths: 50 M, 300 M

Email: office@phoenixtapes.ro
Site: www.phoenixtapes.ro