Phoenix Tapes®
Simbolul Calității

Street Drumul Gilaului no. 5N
District 4, Bucharest
E-mail: office@phoenixtapes.ro
Phone: +4 021.335.1172
Mobile: +4 0729.012.783

# TECHNICAL DATA SHEET 8725

## PRODUCT OVERVIEW

Double sided adhesive tape for permanent bonding with a thick carrier of white hemp fabric. The tape is intended for difficult bonding applications.

## PRODUCT CONSTRUCTION

- **Backing:** Cloth
- **Adhesive:** Hot melt based
- **Liner:** yellow/dark yellow release paper
- **Adhesive/Liner thickness:** 200/80 micron

## TYPICAL PHYSICAL PROPERTIES:

- **Thickness (adhesives+cloth):** 200 mic. ± 10 micron
- **Thickness of release paper:** 80 mic., 80g/m$^2$
- **Tack rolling ball:** 20#
- **Peel Adhesion to steel (180°C):** 15N/25mm
- **Tensile Strenght:** 60N/25mm
- **Elongation:** 5%
- **Application temperature:** 10°C to 35°C
- **Temperature resistance:** 0°C to 60°C

## PACKING:

**Core I.D.:** 5” (76mm±1)
**Log Roll:** 1020mm x 50M
**Packaging:** Wrapped with corrugated cardboard

## REMARKS

(1) The data above are typical results and subject to change without notice
(2) Tolerance: Weight and Thickness: ±10%; Width: ±3mm; Length: Cut Roll & Log Roll ±0.3m; Log roll ±0.5%.
(3) The products should be stored at room temperature, be kept away from wet and/or heat source.
(4) It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
(5) The users should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for their special purpose and technique.

## SUGESTED APLICATIONS

- Mounting carpets and rugs
- Laser engraving, CNC Router projects
- Household renovation

## NOTE:

All data contained in this document are average values, they should not be used for specification purpose. All statements, technical information and recommendations contained are base upon tests that we believe are reliable, but we are strongly recommend clients should do their own tests and decide whether the product is fit for a particular purpose or the method of application.

## IMPORTANT:

Phoenix Invest makes no other warranties, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or any implied warranty arising out of a course of dealing, custom or usage of trade.

## REMEDY & LIMITATION OF LIABILITY:

If the Phoenix Invest product is proved be defective within the warranty period, your exclusive remedy and Phoenix Invest's and seller's sole obligation will be, at Phoenix Invest's to replace or refund the purchase price.

## STORAGE

Products should be stored at temperature 10°C to 35°C and relative humidity 55% ±10%.
The shelf life is 2 (two) years. Avoid prolonged exposure to direct sunlight.

## AVAILABILITY

**Widths:** 6 mm, 9 mm, 12 mm, 25 mm, 50 mm, 100 mm (other widths available)
**Lengths**: 50 M

Email: office@phoenixtapes.ro
Site: www.phoenixtapes.ro