Phoenix Tapes®
Simbolul Calității

Street Drumul Gilaului no. 5N
District 4, Bucharest
E-mail: office@phoenixtapes.ro
Phone: +4 021.335.1172
Mobile: +4 0729.012.783

TECHNICAL DATA SHEET

PACKAGING TAPE Eco Solvent

MAIN FEATURES
Carrier: polypropylene foil (BOPP)
Glue: eco solvent
Color: honey brown

DESCRIPTION

The packaging tape ECO SOLVENT thanks to the modified acrylic glue has very good adhesion. The tape ECO SOLVENT is UV and aging resistant. During time its adhesion and strength is even better. It is perfect to use it for boxes with long term storage.

TECHNICAL SPECIFICATION

Feature	Value	Unit	Tolerance
Total thickness	47	µ	± 5%
Carrier (BOPP) thickness	28	µ	± 5%
Glue thickness	24	µ	± 5%
Length	60	m	± 2%
Width	48	mm	± 0,5 mm
180° Steel Peel Adhesion test	2,1	N/cm	± 9%
180° Box Peel Adhesion test	1,3	N/cm	± 9%
Tensile strength	140	MPa	Not less than
Extensibility	100	%	Not less than

NOTE:

All data contained in this document are average values, they should not be used for specification purpose. All statements, technical information and recommendations contained are base upon tests that we believe are reliable, but we are strongly recommend clients should do their own tests and decide whether the product is fit for a particular purpose or the method of application.

IMPORTANT:

Phoenix Invest makes no other warranties, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or any implied warranty arising out of a course of dealing, custom or usage of trade.

REMEDY & LIMITATION OF LIABILITY:

If the Phoenix Invest product is proved be defective within the warranty period, your exclusive remedy and Phoenix Invest's and seller's sole obligation will be, at Phoenix Invest's to replace or refund the purchase price.

STORAGE

The shelf life recommended is 24 months.
Product should be stored between 5°C and 35°C. The ideal temperature for long storage periods is 18°C to 20°C.

Email: office@phoenixtapes.ro
Site: www.phoenixtapes.ro