Str. Drumul Gilaului, Nr. 5N (Incinta Horting)

Sector 4, Bucuresti

E-mail: office@phoenixtapes.ro

Phone: 021.335.1172

Mobile: 0729.012.783

TECHNICAL DATA SHEET 3819

PRODUCT OVERVIEW

Is a permanent polypropylene tape on a white paper release liner using a high performance permanent rubber adhesive.

PRODUCT CONSTRUCTION

- **Liner:** 90g siliconized paper liner
- **Carrier:** 18g polypropylene
- **Adhesive:** synthetic rubber based with 33gsm on both open and closed sides
- **Adhesive / Liner thickness:** 100/40 micron

PERFORMANCE PROPERTIES

- **Peel adhesion to steel:** (24-hour dwell) protected 1100 N/M open 1100 N/M
- **Shear adhesion to steel:** protected 25 hours open 25 hours
- **Service temperature range:** -20°C to 65°C
- **Recommended application temperature:** 5°C to 50°C
- **Shelf life:** Recommended 24 months from supply

AVAILABILITY

- **Widths:** 6 mm, 9 mm, 12 mm, 25 mm, 50 mm,100 mm (other widths available)
- **Lengths:** 50 M

Email: office@phoenixtapes.ro

Site: www.phoenixtapes.ro